

⚠ WARNING

1. Read all instructions for future reference.
2. Follow all warnings and instructions marked on the product.
3. Do not stand on the VersaHaul.
4. Do not ride any vehicle while loading onto the VersaHaul.
5. Always store the VersaHaul carrier in a safe place.
6. Never exceed vehicle tongue weight ratings.
7. Only use VersaHaul with Class 3 or 4 hitch. Most Class 3 hitches limit the VersaHaul to 500 lbs. total hauling capacity.
8. Improper use, storage or installation of carrier could result in death or serious injury.
9. Do not put any VersaHaul on a 5th wheel trailer or any other kind of trailer.
10. **VH-90 carrying capacity is limited to 700 lbs. max. Your vehicle suspension and hitch may limit the hauling capacity of the carrier.** For more information on vehicles and hauling capacities, visit www.versahaul.com.

LIMITED WARRANTY

The Limited Warranty on the VersaHaul Carrier.

BNK, INC warrants the carrier and related components. This warranty applies to any part found to be defective due to material and/or workmanship when inspected at the factory of BNK, Inc., Winamac, IN. BNK Inc. will, at its option, repair or replace defective parts to the original purchaser at no charge other than transportation. Sale receipt as proof of date of purchase is required, which will be returned. BNK, Inc. assumes no liability for labor charges made in performance of this warranty.

The warranty periods are as follows from date of purchase:

CARRIER FOR 1 YEAR, VOID IF: frame is broken or bent due to abuse. example: (underside scraped abusively)

ALL WARRANTIES ARE VOID IF: the carrier has been rented, used under abnormal conditions, or subjected to abuse, misuse, neglect, or improper maintenance.

All warranties should be handled at point of purchase unless other arrangements are made.

BNK, Inc. is not liable for any damage claim or liability claim, personal or otherwise resulting from operation of this carrier in any way. All transportation charges for items returned for warranty evaluation and/or replacement are to be borne by the customer.

For one (1) year from the date of purchase, BNK, Inc. will repair or replace for the original purchaser, without charge, any part or parts are manufactured by BNK, Inc. and found, upon examination at our factory in Winamac, to be defective in materials and/or workmanship.

All transportation charges on parts submitted for replacement under this warranty must be borne by the purchaser. This warranty does not apply to parts not manufactured by BNK, Inc. Their manufacturer may warrant these items. This warranty does not apply to any part which has been damaged by accident, alteration, abuse, improper adjustment, normal wear, or any other cause beyond our control.

Use of replacement parts other than genuine BNK, Inc. parts may impair the safety of your machine and void this warranty.

IMPORTANT

THIS WARRANTY IS VOID UNLESS THE PRODUCT REGISTRATION CARD IS FILLED OUT COMPLETELY AND RETURNED TO THE FACTORY AT WINAMAC, IN. WITHIN TEN (10) DAYS OF PURCHASE.

OUR WARRANTY COVERS OUR PRODUCT FOR ONE YEAR. WE ARE NOT ABLE TO EXCHANGE USED VERSAHAUL CARRIERS FOR REFUNDS OR NEW CARRIERS.

PARTS

NOTE: VersaHaul is attached with your standard Hitch Pin (not included).



TOOLS



Step 1



Insert the Tie Down Loops into the Main Rail and fasten them with the $\frac{5}{16}$ " x $\frac{3}{4}$ " Carriage Bolts, Flat Washers, Lock Washers, and Nuts in that order.



Bottom view: tighten with a $\frac{1}{2}$ " Wrench.

VH-90 in use.



Assembled VH-90 Carrier



Remove Reflector backing and affix Reflectors as shown.

Step 2

Insert the Main Tube into the Main Rails and fasten with the $\frac{3}{8}$ " x $1\frac{1}{4}$ " Bolts. Note: Make sure the hole is on the bottom of the Main Tube to insure proper assembly.



Step 3



Insert the $\frac{5}{16}$ " x $\frac{3}{4}$ " Bolt through the Wheel Stop and Main Rail.




Tighten the $\frac{5}{16}$ " Nut from below.

Insert the Wheel Stop into the two slots on the top of the Main Rail and fasten with $\frac{5}{16}$ " x $\frac{3}{4}$ " Bolt, Flat Washer, Lock Washer, and Nut.

Step 4

As a final safety precaution, install the $\frac{5}{16}$ " x $\frac{1}{2}$ " Bolt into the end of the Main Tube. Lock the Bolt into place with a Lock Washer and Nut.



ATTACHING YOUR VERSAHAUL



To attach the assembled VersaHaul to your class III or IV 2" receiver, first place the Anti-Tilt Lock Bracket as shown on the Main Tube. Be sure the flat side of the Bracket is facing the carrier. Insert the unit into your receiver. Insert hitch pin and on opposite side insert hair pin. Push the Lock Bracket all the way against the receiver then tighten all three $\frac{3}{8}$ " x $1\frac{1}{4}$ " hex head screws with the $\frac{5}{16}$ " Socket.

SPECIAL FEATURES



VH-90 Ramp Option is available for Purchase. It is not included.



The Taillight Kit is also available for purchase. It is not included.

NOTE: WHEN ATTACHING STRAPS TO TIE-DOWN LOOPS

When attaching the tie down straps, securely hook the straps from the center of the bumper bar to the eyelets located on the Tie Down Loops. Be sure to evenly tighten the straps on both sides of the ATV/Go-Kart. Go-Karts and ATVs must be strapped in on the front as well as the rear.